ILS or LOC RWY 25

FORT SMITH RGNL (FSM)

LOC I-FSM	APP CRS	Rwy Idg	8000
111.3	256°	TDZE	446
		Apt Elev	469

T A ASR — Circling not authorized NW of Rwys 7 and 19 for Cat E. Circling to Rwy 1 NA at night. # Visibility Cat A/B/C/D RVR 1800 authorized with the use of FD or AP or HUD to DA. Circling Cat E NA when R-2401B active.

MALSR

MISSED APPROACH: Climb to 2500 direct JEMBO LOM and hold. (TACAN aircraft climb to 1200 then climbing left, then to 4000 via FSM R-232 to SPIRO Int/15 DME and hold southwest, right turn, 052° inbound.)

ATIS	RAZORBACK APP CON*	FORT SMITH TOWER*	GND CON	CLNC DEL	UNICOM
126.3	120.9 343.75	118.3 (CTAF) L 323.175	121.9 275.8	133.85 278.3	122.95

* Not authorized when Restricted Area R-2401 or R-2402 in effect.

** All maneuvering must be completed to the north side of approach course. Standard width not provided between non-maneuvering side of approach course and R-2401 and R-2402.

(IAF) AYUWU FSM 10 R-359 3100 NoPT FSM 10 Arc

FORT SMITH 110.4 FSM Chan 41

LOCALIZER 111.3 I-FSM

LOM/IAF WIZER 223 FS

RADAR

LR-076 031° 076° 256° R-088 OCEXA FSM 10 LR-100 R-120 2700 (7.4)

R-232 077° 257° 052° SPIRO FSM 15 232° LOM JEMBO 311 GK

R-2401B R-2401A R-2402 R-195 *3100 NoPT FSM 10 Arc *3100 285° (24.8) MAGGA

MSA FS 25 NM 4000

10 NM (IAF) UXADY FSM 10 *3100 357° (19.8) SISCO

ADF REQUIRED

ELEV 469 D

256° 6.8 NM from FAF

8000 X 150 5002 X 150 25 0.5% DOWN 531 TDZE 446

2500 GK 311

LOM INT/RADAR Remain within 15 NM 076° 2697 3100 256° 2700 GS 2.96° TCH 56

6.8 NM

HIRL Rwy 7-25 L
MIRL Rwy 1-19 L

FAF to MAP 6.8 NM

Knots	60	90	120	150	180
Min:Sec	6:48	4:32	3:24	2:43	2:16

CATEGORY	A	B	C	D	E
S-ILS 25	# 646/ 24 200 (200-½)				
S-LOC 25	960/24 514 (500-½)		960/50 514 (500- 1)	960/60 514 (500-1¼)	
CIRCLING	1140-1 671 (700-1)		1140-2 671 (700-2)	1140-2¼ 671 (700-2¼)	1200-2½ 731 (800-2½)

SC-1, 19 NOV 2009 to 17 DEC 2009
SC-1, 19 NOV 2009 to 17 DEC 2009